

MATERIAL SAFETY DATA SHEET

Product Identity: **RCBS BULLET LUBRICANT**
See page 3 for product stock numbers.

Manufactured by: Ammunition Accessories Inc
Onalaska Operations
Box 39
Onalaska, WI 54650
Telephone #: (608) 781-5800
CHEMTREC #: 1-800-424-9300 **DAY OR NIGHT**

MSDS #.903
Prepared by: RLZ
Date of Preparation: March 1, 2005
Supersedes MSDS Dated: July 8, 2003

SECTION I - PRODUCT INFORMATION

TRADE NAME: RCBS Bullet Lubricant
CHEMICAL NAME & SYNONYMS: Lubricant Mixture
C.A.S.REGISTRY #: NA
CHEMICAL FAMILY: NA
FORMULA: NA
MOLECULAR WEIGHT: NA

SECTION II - HAZARDOUS INGREDIENTS

<u>INGREDIENT</u>	<u>CAS #</u>	<u>TLV LEVEL/PEL LEVEL</u>
Paraffin Wax		2.00mg/m ³ fumes if generated
Beeswax	8012-89-3	NE
Microcrystalline blend		NE
Dye*		
(*Contains Dimethyl Benzene	1330207	100ppm)

SECTION III - PHYSICAL DATA

BOILING POINT (DEG C): NA	SPECIFIC GRAVITY (60 deg F): Approx. 0.95
FREEZING POINT (DEG C): NA	PERCENT VOLATILE by VOLUME: < 0.1
VAPOR PRESSURE: Unknown	EVAPORATION RATE(nBuAc): Slight
pH: 1% solution: NA	VAPOR DENSITY (AIR=1): Heavier than air
VISCOSITY: Not determined	PHYSICAL STATE (60 DEG F): solid
SOLUBILITY IN WATER: Nil	
APPEARANCE & ODOR: Green colored waxy substance with an odor of honey and balsam. Slight hydrocarbon odor.	

NA = Not Applicable

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): Approx. 400° F AUTO IGNITION TEMP: Unknown

FLAMMABLE LIMITS: LEL NA UEL: NA

EXTINGUISHING MEDIA: Carbon dioxide, alcohol or foam extinguisher. Use water to cool exposed product.

SPECIAL FIRE FIGHTING PROCEDURES: Water may cause spread of flames as burning material may float of water. Wear self-contained breathing apparatus.

UNUSUAL FIRE & EXPLOSION HAZARDS: None noted.

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: Not determined for mixture. See section II for ingredients.

PRIMARY ROUTE OF EXPOSURE: If hot, burns on skin.

EFFECTS OF OVEREXPOSURE (ACUTE):

EYE CONTACT: Prolonged exposure to fumes or vapors may cause tearing. Contact with molten material may cause thermal burns.

SKIN CONTACT: If molten, will cause thermal burns.

INHALATION: Solid material is not volatile so exposure is unlikely. If working with molten material, may cause irritation of nose and throat. Fire may produce flames which are acrid.

INGESTION: Could cause irritation of digestive tract.

EFFECTS OF OVEREXPOSURE (CHRONIC): See eye contact above. May aggravate preexisting respiratory problems if prolonged contact with fumes from molten material.

EMERGENCY AND FIRST AID PROCEDURES:

EYE CONTACT: Flush with plenty of water for 10-15 minutes. Get medical attention if splashed with molten material.

SKIN CONTACT: If molten material, cool first with cold water. Then treat for thermal burns. Seek medical attention. Wash skin with soap and water.

INGESTION: Drink water to dilute effect. If digestive tract irritation develops or persists, seek medical attention.

INHALATION: If irritation develops from vapors emitted by molten material, remove from source of vapors. Remove to fresh air. Seek medical attention if irritation persists. Give artificial respiration if necessary.

CARCINOGEN CONTENT

% PPM INGREDIENT

IARC No

NTP No OSHA No

SECTION VI - REACTIVITY DATA

STABILITY: STABLE UNSTABLE

CONDITIONS TO AVOID: Flames

INCOMPATIBILITY: Oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and carbon dioxide.

HAZARDOUS POLYMERIZATION: MAY OCCUR WILL NOT OCCUR

SECTION VII - SPILL & DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Clean up spill. Mineral Spirits will remove from floor. Dispose of as you would solid or organic materials.

WASTE DISPOSAL METHOD: Comply with state, federal, and local regulations for solid organic materials.

SECTION VIII - SPECIAL PROTECTION INFORMATION

CONSULT SAFETY EQUIPMENT DISTRIBUTOR

RESPIRATORY PROTECTION: Not necessary for ambient temperature product. If product is heated, organic vapor filter should be used.

VENTILATION: General local exhaust

PROTECTIVE GLOVES: If working with molten product, protective gloves should be used if splash is likely to occur.

EYE PROTECTION: Splash goggles.

OTHER PROTECTIVE EQUIPMENT: If working with molten product, use protective apron.

SECTION IX - STORAGE & HANDLING PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not expose to flame or store in hot area. Lube sticks may lose their shape, making them hard to use.

PRECAUTIONS DURING USE: Use good personal hygiene habits. Wash hands after use and before eating, drinking or smoking.

SECTION X - TRANSPORTATION & REGULATORY INFORMATION

PROPER SHIPPING NAME: NA

CLASS: Not a hazardous material

IDENTIFICATION #: NA

ERG # NA

LABEL: None required

DOT PROPER SHIPPING NAME: NA

DOT CLASS: NA

HMIS Ratings	HMIS RATING KEY	PRODUCT NAME AND SIZE	STOCK NUMBER
HEALTH 1	4 Severe Hazard	RCBS Bullet Lube (1.4 oz.)	40817 / 80008
FLAMMABILITY 0	3 Serious Hazard		
REACTIVITY 0	2 Moderate Hazard		
	1 Slight Hazard		
	0 Minimal Hazard		

For chemical emergency, spill, leak, fire, exposure or accident call:

Inside US: CHEMTREC: 1-800-424-9300 **DAY OR NIGHT**

Outside US: CHEMTREC: 010-202-483-7616 **DAY OR NIGHT**

This information is to the best of Ammunition Accessories, Inc. knowledge and belief, accurate and reliable. However, no representation, warranty or guarantee is made to its accuracy, reliability or completeness. However, since conditions of use are out side our control it should not be taken as a warranty or representation for which Ammunition Accessories, Inc. assumes legal responsibility. This information is provided solely for your consideration, investigation and verification. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use.